



- 特長: 1、SCE225型傳遞力矩約為SCE200型1.5~2倍。  
 2、內外徑尺寸同SCE200型。  
 3、自動對心功能。

尺寸、性能 輪殼內徑表面受面壓 (P<sub>B</sub>) 時的最小外徑 φK (B ≥ 2 × L<sub>1</sub>, b ≥ L, C ≥ d/2)

※(MPa)

規格	L <sub>2</sub> mm	L <sub>1</sub> mm	L mm	可傳遞力矩		面壓力		鎖緊螺絲			拆卸螺牙孔數	輪殼材料 σ <sub>0.2</sub> 與 外徑 φK 之最小值 (mm)						重量 kg	J × 10 <sup>-5</sup> Kg·m <sup>2</sup>	
				扭力 (M) N·m	推力 (F) KN	軸 (Ps) MPa	孔 (P <sub>B</sub> ) Mpa	個數 (N)	尺寸 (ds × l)	扭力 (Ms) N.m		150※	200※	250※	300※	350※	400※			
SCE225 d × D mm												FC250	FC350	FCD400	FCD450	FCD500	FCD600			
												SS400	SS490	SC410	SC480					
												S200.N	S200.N	S35C-N	S45C-N	S55C-N				
45 × 75	64	56	72	3100	137	162	97	8	M8 × 50	40	4	113	102	96	92	89	87	1.42	136	
48 × 80	64	56	72	3310	137	152	91	8	M8 × 50	40	4	118	106	100	97	94	92	1.62	176	
50 × 80	64	56	72	3440	137	146	91	8	M8 × 50	40	4	118	106	100	97	94	92	1.54	171	
55 × 85	64	56	72	3790	137	132	86	8	M8 × 50	40	4	122	111	105	102	99	97	1.65	213	
60 × 90	64	56	72	5170	172	152	101	10	M8 × 50	40	5	139	124	116	111	108	105	1.78	260	
65 × 95	64	56	72	5600	172	140	96	10	M8 × 50	40	5	143	128	121	116	113	110	1.89	314	
70 × 110	78	70	88	9660	276	167	106	10	M10 × 65	80	5	173	153	143	137	133	130	3.46	736	
75 × 115	78	70	88	10300	276	155	102	10	M10 × 65	80	5	178	158	148	142	138	135	3.65	861	
80 × 120	78	70	88	13200	330	175	117	12	M10 × 65	80	6	201	174	161	153	148	144	3.84	1000	
85 × 125	78	70	88	14000	330	165	112	12	M10 × 65	80	6	205	179	166	158	153	149	4.04	1154	
90 × 130	78	70	88	14900	330	155	108	12	M10 × 65	80	6	207	182	170	162	157	154	4.23	1323	
95 × 135	78	70	88	15700	330	147	104	12	M10 × 65	80	6	211	187	175	167	162	158	4.42	1508	
100 × 145	100	90	112	24100	482	159	110	12	M12 × 80	140	6	234	205	191	182	176	172	6.80	2635	
110 × 155	100	90	112	26500	482	144	102	12	M12 × 80	140	6	240	213	199	191	185	181	7.35	3320	
120 × 165	100	90	112	33800	563	154	112	14	M12 × 80	140	7	268	235	218	208	201	196	7.90	4113	
130 × 180	116	104	130	42300	650	143	103	12	M14 × 90	220	6	279	248	232	222	216	211	11.1	6832	
140 × 190	116	104	130	53200	760	155	114	14	M14 × 90	220	7	311	272	252	240	232	226	11.8	8215	
150 × 200	116	104	130	65200	868	165	124	16	M14 × 90	220	8	347	297	273	259	249	242	11.5	9778	
160 × 210	116	104	130	69500	868	155	118	16	M14 × 90	220	8	351	305	281	268	258	252	13.3	11530	
170 × 225	146	134	162	87400	1028	134	101	14	M16 × 110	340	7	346	308	289	277	268	263	19.6	19440	
180 × 235	146	134	162	105700	1174	144	110	16	M16 × 110	340	8	381	334	310	296	286	279	20.6	22510	
190 × 250	146	134	162	111600	1174	137	104	16	M16 × 110	340	8	390	346	323	309	300	293	23.8	29290	
200 × 260	146	134	162	117500	1174	130	100	16	M16 × 110	340	8	398	355	333	319	310	303	24.9	33420	

\*傳遞扭力與推力為最大值。 \*輪殼外徑最小值，φK不含安全係數。